



999.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel® Skylake/Kabylake Processor (TDP 65W)
- 2 \* DDR4 SODIMM Up to 32 GB
- 2 \* USB2.0, 4 \* USB3.0, 1 \* HDMI, 4 \* RJ45, 1 \* COM(RJ45 TYPE), 1 \* GPIO, 1 \* 2.5" DRIVE
- Support TPM1.2/2.0 (option)
- M/B Form Factor : Mini ITX (170x170mm)
- 1U 200W FLEX Power

|                 |                                                                                                                                                    |
|-----------------|----------------------------------------------------------------------------------------------------------------------------------------------------|
| MB Model        | – JNF795-Q170 / Mini ITX                                                                                                                           |
| Part No.        | – HBJC160F795-Q170S                                                                                                                                |
| BIOS            | – AMI Flash ROM                                                                                                                                    |
| CPU/Chipset     | – Intel® LGA1151 SKylake/Kabylake Processor (TDP 65W)<br>– Intel® Q170 chipset                                                                     |
| Memory          | – 2 * SO-DIMM DDR4 (Max 32 GB)                                                                                                                     |
| Graphics        | – Intel® HD Graphics                                                                                                                               |
| Storage         | – 1 * 2.5" SATA 6Gb/s_ internal drive bay<br>– 1 * mSATA (Full size mini-PCIE slot)                                                                |
| Network         | – 4 * Intel Gigabit LAN (1 * i219LM, 3 * i211AT)<br>– 1 * Half-size mini-PCIE slot<br>– 1 * M.2-2230 slot (for WIFI module / Optional)             |
| Rear Panel I/O  | – 4 * USB 3.0<br>– 1 * HDMI 1.4 (Max Resolution : 4096×2304@24Hz)<br>– 4 * RJ45<br>– 1 * RS232 (RJ45 TYPE)<br>– 1 * GPIO (8 bit)<br>– 1 * AC input |
| Front Panel I/O | – 1 * Power button, 1 * Reset button<br>– 1 * Power LED, 1 * HDD LED<br>– 2 * USB 2.0                                                              |
| Power Source    | – 1U 200W FLEX POWER<br>– AC 90~240V input                                                                                                         |
| Compliance      | – CE, FCC, LVD, RoHS                                                                                                                               |
| Temperature     | – Operating Temperature: 0 ~ 50° C<br>– Storage Temperature: -10 ~ 70° C                                                                           |
| Dimensions      | – 430 (W) x 452 (D) x 44 (H) mm                                                                                                                    |
| Packing         | – Net Weight: 4.0KG<br>– Gross Weight: 4.8KG<br>– Color Box dimension: 560 (W) * 600 (D) * 140 (H) mm                                              |
| OS Support      | – Windows 7, Windows 8.1, Windows 10, Linux                                                                                                        |
| Warranty        | – 2 Year limited warranty                                                                                                                          |