



469.00 EUR

incl. 19% VAT, plus [shipping](#)

- Quad-Channel !
- Extended Temperature !
- -40 to 85°C !

Support:  [Specifications](#)

The DarkCrystal SD Capture Mini-PCIe Quad simultaneously preserves up to four channels from multiple composite input sources, reducing system costs. DarkCrystal SD Capture Mini-PCIe Quad makes use of exclusive hardware design guarantying fast response and solid performance for high-density SD capture or encoding demands.

The DarkCrystal SD Capture Mini-PCIe Quad simultaneously preserves up to 4 channels from multiple composite input sources, reducing system costs.

- Supports extended operating temperatures from -40 to 85°C
- Video capture with composite input
- 4-channel concurrent capture solution
- Standard minicard dimension
- Mainstream programming languages supported
- DirectShow compatible

Module Type	PCI Express Minicard
Input	4-ch Composite Audio(L/R)
Video Resolution	NTSC (29.97Hz): 720 x 480, 640 x 480, 360 x 240, 320 x 240, 180 x 120, 160 x 120 PAL (25Hz): 720 x 576, 640 x 480, 360 x 288, 180 x 144
Color Adjustment	Brightness, Contrast, Hue (NTSC only), Saturation
Operating Environment	Temperature: -40 to +85 ■ Humidity: 0 to 90% RHNC

Storage Environment

Temperature: -50 to +85 ■

Power Requirement

Humidity: 0 to 90% RHNC

Dimensions (L x W)

1.13W

50.95 x 30mm

System Requirements

CPU

Intel® Pentium®4 3.0 GHz

Memory

AMD Athlon™ 64 3200+

VGA

512 MB RAM

Sound Card

VGA card with support for DirectX9.0c or above

Supported OS

Yes

Windows 7/8.1/10 (32/64 bits), Linux (32/64 bits)*